



Catalogue
FOOD SERVICE

FMV

Zone:

Item:

Chapter
REFRIGERATION

Specific Model
CUP-11G1/1 230V 1N 50Hz

19089485

07/11/2025

The photo may show the standard model and not the configured one

DENOMINATION:

Concept gastronorm GN 1/1 refrigerated upright, single body with 1 door.

DESCRIPTION :

- Interior constructed with AISI-304 stainless steel exterior in food grade stainless steel.
- 60 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Removable guiding rails construction with 18 grid level position per each full door with 70 mm distance among them.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
- Pivotal panel with better access to control that facilitates service, thus enlarging the useful life of the equipment.
- Automatic evaporation of defrost water.
- Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (130 mm - 200 mm) to enable convenient cleaning.
- Low energy consumption LED lighting horizontally located in the interior of compartment.
- Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Removable and height adjustable epoxy coated GN 1/1 grids with a maximum loading capacity of up to 40 kg.
- Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection.
- Defrost by compressor stop.

POSSIBLE OPTIONS :

- 60 Hz
- Door frame resistance
- Locks
- Opposite Opening

DIMENSIONS



X Width	490 mm	X Gross width	770 mm
Y Depth	700 mm	Y Gross depth	565 mm
Z Height	2010 mm	Z Gross height	2100 mm
Net Weight	102,0 kg	Gross Weight	115,0 kg
Net Volume	1,122 M3	Gross Volume	0,910 M3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,205 KW
Voltage	230V - 1N
Phases	1N
Electric frequency	50Hz
Amperage (A)	1 A

COLD TECHNICAL SPECIFICATIONS

Energy Efficiency Index	73,400 %
Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,361 KW
Gas type	R-600a
GWP	3,000
Cooling gas load	0,100 KG
Gross internal volume	320,000 L
Noise level	53,000 DB
Condensation system	Vent.
Model Type	Vertical cabinet
Annual elec. consumption	726,400 KWH
Power consumption 24h	1,990 KWH
Refrigeration net.vol	231,000 L
Frozen net.vol	0 L
IEE	73,000
Clasif. Energy efficiency	D

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
Single-phase 230V wiring	2X1+T-2A



Catalogue
FOOD SERVICE

FMV

Zone:

Item:

Chapter
REFRIGERATION
Specific Model
CUP-11G1/1 230V 1N 50Hz

19089485

07/11/2025

The photo may show the standard model and not the configured one

- Remote group
- Stainless Backing
- UK plug
- Wheels Kit (Factory Assembly)

SUPPLIED ACCESSORIES:

- 19097778 GN 1/1 epoxi grid for GN 1/1 refrigerated uprights. 3ud.
- 19100845 Tray support guides for gastronorm GN 1/1 refrigerated uprights. 3ud.

POSSIBLE ACCESSORIES:

- ACCESSORIES FOR REFRIGERATION
- Gastronorm grids

OTHERS

Number of doors 1,000



Catalogue
FOOD SERVICE

FMV

Zone:

Item:

Chapter
REFRIGERATION
Specific Model
CUP-11G1/1 230V 1N 50Hz

19089485

07/11/2025

The photo may show the standard model and not the configured one

