



**Catalogue**  
**FOOD SERVICE**  
**Chapter**  
**REFRIGERATION**

**Specific model**  
**CUD-12G/N 230V 1N 50Hz**

19089472

23/03/2022

**DENOMINATION:**

Refrigerated cabinet with freezing compartment - Concept Gastronorm with 2 doors (1 freezing), at 50Hz.

**DESCRIPTION :**

- Structure built with AISI-304 stainless steel.
- 60 mm, 40 kg/m<sup>3</sup> injected polyurethane insulation.
- Embedded inner tray slides. Storage trays at 23 different levels 55 mm from each other.
- Forced draught cooling system with hermetically sealed compressor.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- Opened door delay alarm.
- Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
- Built-in drainage to get rid of waste liquids inside the unit.
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
- Tested in climatic class 4..
- Inner LED lights with power switch (in refrigerated cabinets and now also in freezing units).

'Refrigeration cabinets with freezing compartment.

- Equipment: 3 drawers in sanitary PVC Independent hermetic compressor with ventilated condenser.
- Evaporator with copper pipe and aluminium cooling fins.
- Environmentally-friendly refrigerant R-290. Forced draught refrigeration
- Automatic evaporation of frost water
- Operational temperature: -18 °C, -22 °C.

**POSSIBLE OPTIONS :**

- Stainless Backing
- Wheels Kit (Factory Assembly)
- British plug
- Door frame resistance
- Opposite Opening


**POSSIBLE ACCESSORIES :**

- REFRIGERATION
- ACCESSORIES
- GASTRONORM GRIDS

**SUPPLIED ACCESSORIES:**

- 12033784 Drawer for Frozen product - 530x540x100 mm 3
- 12036716 Guide for grill GN-1 / 1- central - 612 mm - 1 piece 8
- 12037948 Guide for Frozen compartment (662 mm) 1 piece 8
- 12037958 GN-2/1 GRID made in Epoxi (650x530) 1

**DIMENSIONS**



X Width	693 mm	X Gross width	730 mm
Y Depth	826 mm	Y Gross depth	880 mm
Z Height	2008 mm	Z Gross height	2027 mm
Net Weight	167,0 kg	Gross Weight	175,0 kg
Net volume	1,149 m <sup>3</sup>	Gross volume	1,302 m <sup>3</sup>

**ELECTRICITY TECHNICAL SPECIFICATIONS**

Amperage (A)	4,3 A
Electric frequency	50Hz
Electric power	1,091 kW
Voltage	230V - 1N

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-290
----------	-------

**COLD TECHNICAL SPECIFICATIONS**

Climate class	4
Cooling gas load	98,000 g
Gross internal volume	596 L
Refrigeration power	0,369 kW

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1,5+T - 4 A
--------------------------	---------------

**OTHERS**

Condensation system	Vent.
Number of doors	2





**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
CUD-12G/N 230V 1N 50Hz

19089472

23/03/2022

