



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUD-23G/F 230V 1N 50Hz

19089479

23/03/2022

DENOMINATION:

Refrigerated cabinet with fish compartment - Concept Gastronorm with 2 compartments and 3 doors (1 for fish).

DESCRIPTION :

- Structure built with AISI-304 stainless steel.
 - 60 mm, 40 kg/m3 injected polyurethane insulation.
 - Embedded inner tray slides. Storage trays at 23 different levels 55 mm from each other.
 - Forced draught cooling system with hermetically sealed compressor.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - Opened door delay alarm.
 - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climatic class 4..
 - Inner LED lights with power switch (in refrigerated cabinets and now also in freezing units).
- Refrigerated cabinet with fish compartment.
- Equipment: 3 drawers in sanitary PVC with perforated stainless steel floor
- Independent hermetic compressor with ventilated condenser.
 - Environmentally-friendly refrigerant R-290.
 - Cold plate evaporator.
 - Drain in evaporator tray.
 - Drainage pipe from the chamber to connect to exterior drain
 - Operational temperature: -4 °C, +4 °C.

POSSIBLE OPTIONS :

- Stainless Backing
- Wheels Kit (Factory Assembly)
- British plug
- Door frame resistance

POSSIBLE ACCESSORIES :


- REFRIGERATION
- ACCESSORIES
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12033784 Drawer for Frozen product - 530x540x100 mm 3
- 12034707 Perforated bottom - 530x540 mm 3
- 12036716 Guide for grill GN-1 / 1- central - 612 mm - 1 piece 6
- 12037948 Guide for Frozen compartment (662 mm) 1 piece 14
- 12037958 GN-2/1 GRID made in Epoxi (650x530) 4

DIMENSIONS

X Width	1388 mm	X Gross width	1430 mm
Y Depth	826 mm	Y Gross depth	880 mm
Z Height	2008 mm	Z Gross height	2027 mm
Net Weight	232,0 kg	Gross Weight	245,0 kg
Net volume	2,302 m3	Gross volume	2,551 m3



ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	2 A
Electric frequency	50Hz
Electric power	0,852 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Annual elec. consumption	906,00 kWh
Clasif. Energy efficiency	D
Climate class	4
Cooling gas load	100,000 g
Energy Efficiency Index	53,66 %
Gross internal volume	1301 L
Model Type	Vertical cabinet
Power consumption 24h	2,48 kWh
Refrigeration net.vol	656 L
Refrigeration power	0,436 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 4 A
--------------------------	---------------

OTHERS

Condensation system	Vent.
Number of doors	3





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUD-23G/F 230V 1N 50Hz

19089479

23/03/2022

