

Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
 ACP-2G/C 230V 1N 50Hz

19089538

23/03/2022

DENOMINATION:

Refrigerated central counter - Advance 700 Gastronorm with 4 doors (2+2).

DESCRIPTION :

- Structure built with AISI-304 stainless steel
 - 50 mm, 40 kg/m3 injected polyurethane insulation.
 - Forced draught cooling system inside the room.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
 - Easier loading and unloading thanks to its door self-closing and stay open features.
 - Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
 - Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Interior LED lighting (only for models with glass doors).
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - 10 cm high splashback.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climatic class IV.
- Refrigerated central counters.
 FLEXIBILITY: Doors on both sides for easier reaching in.

POSSIBLE OPTIONS :

- Wheels Kit (Factory Assembly)
- British plug
- Door frame resistance
- Granite worktop
- Locks
- Left group
- Without Countertop
- Panoramic aperture
- Remote group

STANDARD OPTIONS :

- HACCP alarm
- Without breastplate

POSSIBLE ACCESSORIES :


- REFRIGERATION
- ACCESSORIES
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12035781 GN 1/1 grid in enoxy (530x325) 2

DIMENSIONS

X Width	1340 mm	X Gross width	1455 mm
Y Depth	768 mm	Y Gross depth	825 mm
Z Height	850 mm	Z Gross height	1000 mm
Net Weight	107,0 kg	Gross Weight	112,0 kg
Net volume	0,881 m3	Gross volume	1,200 m3



ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	0,93 A
Electric frequency	50Hz
Electric power	0,174 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Climate class	4
Cooling gas load	98,000 g
Gross internal volume	258 L
Refrigeration power	0,361 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Condensation system	Vent.
Number of doors	4



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
ACP-2G/C 230V 1N 50Hz

19089538

23/03/2022

- 12036880 Advance table grill guide - wall and central - 519 mm - 1 piece 8

