

Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
ST-175C 230V 1N 50Hz

19089748

25/03/2022

DENOMINATION:

Snack showcase with curved glass cover.

DESCRIPTION :

- Inner tray made of high quality austenitic stainless steel.
- External cladding with anodised aluminium profile and PVC with glass on the sides.
- Injected polyurethane insulation of 40 kg/m3 density without CFC.
- Capacity to receive 40 mm GN-1/3 trays.
- The versions with remote unit include the refrigeration unit as standard equipment.
- * Its dimensions are 310 x 360 x 240 mm and it must be connected at a maximum distance of 1.5 m.
- Copper tube cold plate evaporator.
- Emergency drain for waste water evacuation.
- Electronic thermostat for temperature control.
- Protected interior lighting.
- Illuminated main switch.
- Working temperature: +4 °C, +8 °C, (ambient 32 °C).
- Curved glass cover (one piece) and glass sliding doors.


POSSIBLE OPTIONS :

- British plug

POSSIBLE ACCESSORIES :

- DISTRIBUTION

DIMENSIONS



X Width	1732 mm	X Gross width	1790 mm
Y Depth	415 mm	Y Gross depth	480 mm
Z Height	270 mm	Z Gross height	480 mm
Net Weight	43,0 kg	Gross Weight	55,0 kg
Net volume	0,194 m3	Gross volume	0,412 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	0,7 A
Electric frequency	50Hz
Electric power	0,106 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Annual elec. consumption	641,31 kWh
Clasif. Energy efficiency	B
Climate class	4
Cooling gas load	73,000 g
Energy Efficiency Index	15,01 %
Power consumption 24h	1,76 kWh
Refrigeration power	0,169 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 2 A
--------------------------	---------------

OTHERS

Colour	Black
Condensation system	Vent.

Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
ST-175C 230V 1N 50Hz

19089748

25/03/2022

