



Catalogue
FOOD SERVICE
Chapter
DISTRIBUTION

Specific model
 FTPY6-2 230V 1N 50/60Hz

19092148

20/05/2022

DENOMINATION:

Ice cream teppanyaki width 610 mm 2 GN 1/1 capacity FTPY6-2 230V 1N 50/60 Hz climate class 4 cold group included refrigerant gas R290

DESCRIPTION :


- Refrigerated top plate ""ice cream teppanyaki"" specially designed to perform live preparations and serve cold desserts (e.g. rolled ice creams, crepes, sherbets, cocktails, chocolate) in front of the guest.
- Manufactured in stainless steel with satin finish. Perimeter flange to prevent overflows.
- Ice cream teppanyaki static refrigeration system by expanded copper coil located in its base.
- Polyurethane insulation with ecological injection, CFC-free, with high-density (40 kg/m³) allowing energy savings by reducing loss of cold air.
- Control panel with digital thermostat, protected by the structure perimeter, avoiding hindrances in their daily use.
- Control panel with 1-meter long cable, allowing to be installed on another element, e.g. furniture under the drop-in element.
- Electronic thermostat, with digital display, to control and regulate the temperature on the ice cream teppanyaki at the desired set point.
- Manual defrost system activated by a button.
- Robust structure with 13 mm thick overlap, once element is dropped-in on the worktop, ensuring cleanness and aesthetics.
- Operating temperature on the ice cream teppanyaki: from -35 °C to -30 °C.

POSSIBLE ACCESSORIES :

- TOOL TO LIFT DROP-IN

DIMENSIONS

X Width	790 mm	X Gross width	820 mm
Y Depth	610 mm	Y Gross depth	895 mm
Z Height	634 mm	Z Gross height	680 mm
Net Weight	49,0 kg	Gross Weight	54,0 kg
Net volume	0,306 m ³	Gross volume	0,499 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,560 kW
Amperage (A)	3,2A
Voltage	230V - 1N
Electric frequency	50/60Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R455A
----------	-------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,305 kW
Climate class	4
Cooling gas load	270,000 g

SERVICE TROLLEY ACCESSORIES

Cut-out Length (mm)	765
Cut-out Width (mm)	585
Capacity (GN)	2 x GN1/1
Working surface long (mm)	630 mm
Working surface width (mm)	510
Working surface height (mm)	30 mm
Plate type	Static refrigerated






Catalogue
FOOD SERVICE
Chapter
DISTRIBUTION

Specific model
FTPY6-2 230V 1N 50/60Hz

19092148

20/05/2022



H • : - 272 mm

W = 610 mm	W = 720 mm
LE : 499 mm	LE : 499 mm
AE : 335 mm	AE : 390 mm

	W = 610 mm	W = 720 mm
	V	V
2GN	585	690