

MODELS: **VMD31S**
VMD37S

VMD31R
VMD37R

Madrid series– Refrigerated modular display case.



VMD25S

Strengths

- ✓ *Combination of different cooling system modules: ventilated, half-static and static. Modules with or without cooled storage. Angles and counters to adapt the line to a space.*
- ✓ *Greater precision in temperature control. Easier to adjust the temperature range we want to achieve.*
- ✓ *All condenser units are tested 100%, in helium chambers to refrigerant leak detections.*
- ✓ *LED lighting incorporated, reducing energetic consumption between 80% and 90% respect to a traditional light bulb.*
- ✓ *Infrico is AENOR audited and certified by internationally recognized firm. ISO 9001:2015 (Quality); ISO 14001:2015 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety). Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7.*

MODEL	Dimensions (mm)			Sides thickness (mm)	Nº Doors	Exposure surface (m²)	Cabinet volume (L)	Gross volume (L)	Temp. regime (°C)	Ref.	Net weight (Kg.)
	Length	Depth	Height								
VMD31R	3125	1150	1290	30 + 30	5	1,73	436	4725	0°C/+6°C	R452	
VMD37R	3750	1150	1290	30 + 30	6	2,1	524	6315	0°C/+6°C	R452	
VMD31S	3125	1150	1290	30 + 30	5	1,73	436	4725	0°C/+6°C	R452	
VMD37S	3750	1150	1290	30 + 30	6	2,1	524	6315	0°C/+6°C	R452	

MODELS: **VMD31S**
VMD37S

VMD31R
VMD37R

Madrid series— Refrigerated modular display case.

STANDARD FEATURES

➤ Modular line

- Different cooling system modules can be combined using complete dividers.
- Designed for meat and precooked and packaged foods, charcuterie, milk products and sandwiches.

➤ Exterior

- Plastic coated steel exterior.
- AISI 304 stainless steel worktop.
- AISI 304 stainless steel exposure surface.
- Lacquered DM decoration.
- Folding secured curved glass.

➤ Interior

- Plastic coated steel interior.
- Enamelled steel base.
- LED lighted middle shelf and exposure surface.
- Storage door clearance of 425x255 mm.

➤ Insulation

- Insulation by free CFC's polyurethane, foam high-pressure injected with density 40 Kg/m³.
- Zero ODP and Low GWP.

➤ Refrigeration

- Temperature and defrost regulated by a digital controller.
- Automatic defrost.
- Ventilated condensation system.
- Forced evaporation system.
- Stainless steel evaporative tray with double vat, one for hot gas and another with electrical heater.
- Climatic class 4 (30°C, 55%RH).

➤ Electrical

- Electrical connection: 230 V / 1 ph / 50 Hz.



OPTIONAL

- ☐ Sliding back doors.
- ☐ Night curtains.
- ☐ Double plane (without storage).
- ☐ Lacquered frontal + sides.
- ☐ Range of decoration colours (consult).
- ☐ Electrical connection 230 V / 1 ph / 60 Hz.
- ☐ Electrical connection 115 V / 1 ph / 60 Hz.

MODEL	Dimensions palletizing (mm)			Pallet weight (Kg.)	Power (W)	Comp. (HP)	Cooling power (W at -10°C)	Consumption (kWh/24h)	Inten. (A)
	Length	Depth	Height						
VMD31R	3288	1200	1500		310	-	2340	4,3	1
VMD37R	3915	1200	1500		370	-	2812	5,2	2
VMD31S	3288	1200	1500		310	-	2340	4,3	1
VMD37S	3915	1200	1500		370	-	2812	5,2	2

Madrid series— Refrigerated modular display case.