



## Catalogue

### FOOD SERVICE

## Chapter

### DISTRIBUTION

## Specific Model

### FPBCF-2 230V 1N 50/60Hz

The photo may show the standard model and not the configured one

19092125

27/06/2023

#### DENOMINATION:

Undercounter refrigerated plate 2 GN 1/1 capacity FPBCF-2 230V 1N 50/60 Hz climate class 4 cold group included refrigerant gas R290

#### DESCRIPTION :

- Refrigerated plate specially designed to be mounted under a countertop, keeping pre-chilled products at optimum temperatures during service time.
- Factory-approved countertop materials include granite and quartz (Silestone®) up to 20 mm. Please contact factory for applications with other materials.
- Top plate aluminum surface for a better diffusion of the cold on the worktop thanks to its high thermal conductivity.
- Total seamless countertop, maximizing hygiene, tightness and aesthetics.
- Expansion joint installation required between countertop refrigerated and neutral areas.
- Top plate refrigeration system by expanded copper coil located in its base.
- Polyurethane insulation with ecological injection, CFC-free, with high-density (40 kg/m³) allowing energy savings by reducing loss of cold air.
- Control panel with 1-meter long cable, allowing to be installed on another element.
- Electronic thermostat, with digital display, to control and regulate the temperature on the worktop at the desired set point.
- Automatic defrost system that minimizes compressor workload and saves energy.
- Operating temperature under countertop: from -25 °C to -30 °C.

#### POSSIBLE ACCESSORIES:

- FOODSHIELD WITH LIGHT
- NEUTRAL FOODSHIELD

#### DIMENSIONS



X Width	611 mm	X Gross width	895 mm
Y Depth	590 mm	Y Gross depth	820 mm
Z Height	477 mm	Z Gross height	680 mm
Net Weight	45,0 kg	Gross Weight	50,0 kg
Net Volume	0,17 M3	Gross Volume	0,50 M3

#### GAS TECHNICAL SPECIFICATIONS

Gas type	R-290
----------	-------

#### ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,205 KW
Amperage (A)	1.69A
Voltage	230V - 1N
Electric frequency	50/60Hz

#### COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,145 KW
Climate class	4
Cooling gas load	72,000 G

#### TECHNICAL FEATURES

Capacity (GN)	2 x GN1/1
Plate type	Static refrigerated
Plate type	Static refrigerated
Ramekin Ø 130mm cap. on top	25,000
Plate Ø 150mm capacity on top	19,000
Ramekin Ø 130mm cap. on top	25,000
Plate Ø 150mm capacity on top	19,000
Plate Ø250 mm capacity on top	7,000
Plate Ø250 mm capacity on top	7,000



**Catalogue**  
FOOD SERVICE



**Chapter**  
DISTRIBUTION

**Specific Model**  
FPBCF-2 230V 1N 50/60Hz

The photo may show the standard model and not the configured one

19092125

27/06/2023



LE : 287 mm

AE : 296 mm

H : - 137 mm

	X	Z
2GN	611	140
3GN	936	465
4GN	1261	790
5GN	1586	1115
6GN	1911	1440

	W	TR
W	476	502
V	77	102