



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Model
EAAFP-801 CR RI 230V 1N 50Hz

19038342

31/08/2020

REFRIGERATED CABINET ADVANCE, EAAFP-801


- Constructed in AISI-304 stainless steel.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- Opened door delay alarm.
- Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
- Built-in drainage to get rid of waste liquids inside the unit.
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- Inner LED lights with power switch.
- It also includes stainless steel back panel.
- 80 mm, 40 kg/m3 injected polyurethane insulation.
- Embedded inner tray slides. Storage trays at 24 different levels 55 mm from each other.
- Forced draught cooling system.
- HACCP system that keeps running logs.
- Acoustic and visual alarm connected to three sensors at strategic spots.
- They provide a total control and block the compressor in case of dirt or failure.
- Removable plastic covered steel grid shelves (GN 2/1) for easy cleaning. Equipment: 3 shelves per large door.
- Locks included as a standard in all doors.
- Working temperature: from -2 °C to +8 °C. This device is designed to be used at ambient temperatures up to 40 °C.
- Electronic expansion valve.
- Number of doors: 1

Options:

- Castor kit (factory assembly).
- Reversible door.
- Door opening pedal (factory assembly).
- "- Heated door frame to avoid condensation in high humidity environments.
- "

DIMENSIONS

X Width	693 mm	X Gross width	730 mm
Y Depth	856 mm	Y Gross depth	880 mm
Z Height	2106 mm	Z Gross height	2185 mm
Net Weight	152,0 kg	Gross Weight	160,0 kg
Net volume	1,210 m3	Gross volume	1,404 m3



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,158 kW
Amperage (A)	0,5 A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,361 kW
Annual elec. consumption	339,00 kWh
Power consumption 24h	0,93 kWh
Gross internal volume	610 L
Refrigeration net.vol	461 L
Climate class	5
Cooling gas load	103,000 g
Clasif. Energy efficiency	A
Energy Efficiency Index	24,84 %
SubFamilia	Vertical cabinet

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-1A
--------------------------	----------

OTHERS

Condensation system	Vent.
---------------------	-------



Catalogue
FOOD SERVICE

Chapter
REFRIGERATION

Model
EAAFP-801 CR RI 230V 1N 50Hz

19038342

31/08/2020

